CREATIVE SOUND CONCEPTS



Contrabass Series CB 15s

Engineered for Impact: Experience Bass Like Never Before!

The CB 15s is a 600 Watt 6th order band-pass subwoofer featuring a 15" LF driver with a 4" voice coil for extended, precise bass. Despite its compact footprint, it delivers High SPL's Bass Output, making it ideal for clubs, performance spaces, and commercial installations.

Grill Less design designed for stealth integration, it can be concealed in stage platforms, furniture, or columns, freeing up floor space. Best paired with CSC tops such as CF 10 MK1, CC 8, ST 3 and ST 12 Mk2/ ST 12t, the CB 15s forms balanced full-range systems with impressive power and vocal clarity.

Its hidden design and strong performance make it perfect where impactful bass must remain discreet.

KEY FEATURES

- Compact, high-performance, band-pass sub-woofer
- Fast, integral wall/ceiling mounting frames
- Vertical and horizontal mounting options
- Easy and fast to install
- Can retrofit in existing venues
- Grill-less design to optimize the performance and colour options

SYSTEM APPLICATIONS

- Lounges and bars
- Gyms
- Museums and A/V spaces
- Hotels
- Homes
- Places of worship
- Music rooms

CREATIVE SOUND CONCEPTS

MODEL NO	CB 15s
Type	Compact, Band pass subwoofer
Frequency Response (1)	45 Hz-150 Hz ± 3 dB
Drivers	LF:1x 15" (375 mm) with a 4" (100 mm) voice coil
Recommended Amplifier Upto	1200 watts
Sensitivity (1 W/1 m)	98 dB
Maximum SPL (9)	123 dB continuous, 129 dB Max
Nominal Impedance	8 ohms
Dispersion	Omni
Crossover	100 Hz active / passive low pass filter
Enclosure	Baltic birch ply
Finish	Non-toxic Textured black paint
Protective Grill	Internal Steel Grill
Connectors	2 x Neutrik NL4
Pin Connections	Input ± 1, Link through: ± 2
Standard Colours	Black
Fittings	Integral feet
Horn	NA
AES Power Handling	600 watts
Maximum/ Continuous/ Program Power	1200 watts
Peak Power	2400 watts
Accessories	Ceiling mount kit
Dimensions - Product (in mm)	(W) 1014 x (H) 393 x (D) 383
Dimensions - Including packing (in mm)	(W) 1023 x (H) 430 x (D) 425
Net weight (kgs)	36
Shipping Weight (kgs)	40

Mid highs measured on-axis in full space @ one watt/1-meter using band-limited pink noise in the en-devour to continuously improve the product with design refinements introduced into existing products. Any current CSC product may differ in some respect from its published description. However, this will always equal or exceed the original design specifications. Every CSC Product is built to the highest standards and tested to ensure that it meets the performance criteria specified.





