

Contrabass Series CB 215s

Engineered for Impact: Experience Bass Like Never Before!

The CB 215s is the powerhouse of the Contrabass range, an 8th order band-pass subwoofer with dual 15" LF drivers powered by 1000 Watts and 4" voice coils.

Built for large-scale venues, it delivers massive low-frequency extension while preserving clarity and punch. Despite its performance, the CB 215s retains the low-profile Contrabass design, allowing discreet integration into stages, steps, and vertical columns.

Ideal for nightclubs, theatres, and touring applications, it is best paired with CF 10 MK1, CF 12 MK2, CF 15, CF 12h MK2, and CC 8 tops, creating full-range systems with unmatched depth and authority. Combining size, power, and stealth, the CB 215s is the ultimate solution for venues demanding maximum bass impact with minimal footprint.

KEY FEATURES

- Compact, high-performance, band-pass 12" or 15" sub-woofer
- Fast, integral wall/ceiling mounting frames
- Vertical and horizontal mounting options
- Easy and fast to install
- Can retrofit in existing venues
- Grill-less design to optimize the performance and colour options

SYSTEM APPLICATIONS

- Lounges and bars
- Gyms
- Museums and A/V spaces
- Hotels
- Homes
- Places of worship
- Music rooms

CREATIVE SOUND CONCEPTS

MODEL NO	CB 215s
Type	Compact, band pass sub-woofer
Frequency Response (1)	45 Hz-150 Hz ± 3 dB
Drivers	LF: 2 x 15" (375 mm) with a 4" (100 mm) voice coil
Recommended Amplifier Upto	2000 watts
Sensitivity (1 W/1 m)	100 dB
Maximum SPL (9)	130 dB continuous, 136 dB Max
Nominal Impedance	4 ohms
Dispersion	Omni
Crossover	100 Hz active / passive low pass filter
Enclosure	Baltic birch ply
Finish	Non-toxic Textured black paint
Protective Grill	Internal Steel Grill
Connectors	2 x Neutrik NL4
Pin Connections	Input :± 1, Link through: ± 2
Standard Colours	Black
Fittings	Integral feet
Horn	NA
AES Power Handling	1000 watts
Maximum/ Continuous/ Program Power	2400 watts
Peak Power	4800 watts
Accessories	NA
Dimensions - Product (in mm)	(W) 1100 x (H) 428 x (D) 642
Dimensions - Including packing (in mm)	(W) 1122 x (H) 475 x (D) 670
Net weight (kgs)	70
Shipping Weight (kgs)	77

Mid highs measured on-axis in full space @ one watt/1-meter using band-limited pink noise in the en-devour to continuously improve the product with design refinements introduced into existing products. Any current CSC product may differ in some respect from its published description. However, this will always equal or exceed the original design specifications. Every CSC Product is built to the highest standards and tested to ensure that it meets the performance criteria specified.





