





CELLO SERIES CF 10 MK1

Compact Design, Massive Impact: Loudspeakers that Deliver

The CF 10 MK1 is a two-way passive loudspeaker designed for compact, powerful reinforcement. It features a 10" LF driver with a 1" compression driver on a 1.7" voice coil, mounted on an 80° × 70° horn for precise coverage.

Built from Baltic birch plywood, it balances portability and durability, making it equally suitable for fixed installations or mobile setups. Its special design reduces heat build-up while maintaining fast transient response, ensuring accuracy across demanding applications from nightclubs to opera houses.

Compact yet versatile, the CF 10 MK1 can also be used as a stage monitor for small bands, offering clarity, punch, and reliability.

KEY FEATURES

- Compact, two-way system
- CF 10 MK1 80° x 70° horn
- Mounting points behind the cabinet
- Large port behind the cabinet
- Can double as a stage monitor & top hat

SYSTEM APPLICATIONS

- A/V applications and presentations
- Live performances
- Clubs reinforcement
- Stage monitoring
- Convention centres
- Auditoriums
- Places of worship
- Ideal for installation and mobile use

CREATIVE SOUND CONCEPTS

MODEL NO	CF 10 MK1
Type	Compact two way full range
Frequency Response (1)	70 Hz-19.5 kHz ± 3 dB
Drivers	LF: 10" (254 mm) with a 2.5" (65mm) voice coil, HF: 1" (25 mm) compression driver with a 1.7" (44 mm) voice coil
Recommended Amplifier Upto	600 watts
Sensitivity (1 W / 1 m)	98 dB
Maximum SPL (9)	122 dB continuous, 128 dB Max
Nominal Impedance	8 ohms
Dispersion	80° x 70°
Crossover	HPF 60Hz full range / 100 Hz with sub
Enclosure	Baltic birch ply
Finish	Non-toxic Textured black paint
Protective Grill	Perforated steel
Connectors	2 x Neutrik NL4
Pin Connections	Input: ± 1, Link through: ± 2
Standard Colours	Black
Fittings	Rear/ Top standard mounting points, Top hat
Horn	Rotatable
AES Power Handling	300 watts / 60 watts
Maximum/ Continuous/ Program Power	600 watts / 120 watts
Peak Power	1200 watts / 240 watts
Accessories	Wall / ceiling mount bracket, Extension pipe
Dimensions - Product (in mm)	(W) 312 x (H) 542 x (D) 309
Dimensions - Including packing (in mm)	(W) 375 x (H) 600 x (D) 380
Net Weight (kgs)	19
Shipping Weight (kgs)	21

Mid highs measured on-axis in full space @ one watt/1-meter using band-limited pink noise in the en-devour to continuously improve the product with design refinements introduced into existing products. Any current CSC product may differ in some respect from its published description. However, this will always equal or exceed the original design specifications. Every CSC Product is built to the highest standards and tested to ensure that it meets the performance criteria specified.





