



CONTRABASS SERIES CR 218s

Engineered for Impact: Experience Bass Like Never Before!

The Contrabass CR 218s is a dual 18" (2 × 450 mm) reflex-loaded subwoofer delivering 1600 Watts of massive low-frequency output. Each driver is equipped with an industry-standard 4" voice coil, ensuring durability and consistent performance in the most demanding applications.

Despite its power, the CR 218s stands at under 475 mm in height, making it suitable for installation under stages or in venues with height restrictions.

Designed as the main system subwoofer for large-scale live events, clubs, and touring rigs, it adds exceptional bass dynamics while improving midrange clarity by offloading the main cabinets.

Perfectly matched with CC 8, CF 10 MK1, CF 12 MK2, CF 15, CF 12h, RR 15h, and RR 212h MK3 tops, the CR 218s delivers a full-range system with unmatched depth, authority, and punch.

KEY FEATURES

- Compact, high-performance
- Reflex-loaded, 18" sub-woofer
- Easy and fast to install
- Can retrofit in existing venues

SYSTEM APPLICATIONS

- Auditoriums
- Concerts and live performances
- Nightclubs and loud bars
- Places of worship

MODEL NO	CR 218s
Type	Compact, Reflex loaded, Subwoofer system
Frequency Response (1)	35 Hz-250 Hz \pm 3 dB
Drivers	LF: 2 x 18" (450 mm) with a 4" (100 mm) voice coil
Recommended Amplifier Upto	3200 watt
Sensitivity (1 W / 1 m)	101 dB
Maximum SPL (9)	133 dB continuous, 139 dB Max
Nominal Impedance	4 ohms
Dispersion	Omni
Crossover	100 Hz active/ passive low pass filter
Enclosure	Baltic birch ply
Finish	Non-toxic Textured black paint
Protective Grill	Perforated steel
Connectors	2 x Neutrik NL4
Pin Connections	Input \pm 1, Link through: \pm 2
Standard Colours	Black
Fittings	Rubber feet
Horn	NA
Nominal/ AES Power	1600 watts
Maximum/ Continuous/ Program Power	3200 watts
Peak Power	6400 watts
Accessories	NA
Dimensions - Product (in mm)	W) 1178 x (H) 474 x (D) 777
Dimensions - Including packing (in mm)	(W) 1195 x (H) 495 x (D) 815
Net Weight (kgs)	73
Shipping Weight (kgs)	80

Mid highs measured on-axis in full space @ one watt/1-meter using band-limited pink noise in the en-devour to continuously improve the product with design refinements introduced into existing products. Any current CSC product may differ in some respect from its published description. However, this will always equal or exceed the original design specifications. Every CSC Product is built to the highest standards and tested to ensure that it meets the performance criteria specified.

