



## **HARP SERIES MI 510**

Unmatched Clarity, Effortlessly Blended

The Harp MI 510 is a compact two-way ceiling speaker with a 6½" LF driver and a coaxially mounted tweeter for enhanced clarity and full-range reproduction. Designed for background and public applications, it provides superb off-axis uniform coverage with seamless intelligibility for both music and voice. Its phase-optimized crossover ensures smooth coupling between drivers, avoiding tonal masking.

Constructed from moisture-resistant materials, it is safe for bathrooms, kitchens, saunas, under outdoor eaves, and even VOG use in home cinemas. Installation is straightforward: cut a hole, feed the wires, and drop in.

With a paintable finish, the MI 510 integrates easily into any interior, offering a discreet, high-quality sound solution that disappears visually while delivering uncompromised performance.

### **KEY FEATURES**

- Compact, high performance two-way ceiling speaker
- High power 40 watt-nominal
- SPL 106 dB
- Frequency response from 75 Hz to 18.5kHz
- Musically accurate with stunning vocal propagation
- Very smooth off-axis response-usable out to 120° (-6 dB)
- Fast, integral hardware

### **SYSTEM APPLICATIONS**

- Distributed audio/public address system
- Component for commercial and retail
- Hotels, shopping malls
- Education and religious establishments
- Hospitals and conference rooms



MODEL NO	MI 510
Type	6½" Ceiling Speaker open Baffle
Frequency Response	75 Hz-18.5 kHz ± 3 dB
Drivers	LF: 1 x 6½" (150 mm) LF + Coaxially mounted Myler HF
Sensitivity (1 W / 1 m)	89 dB
Maximum SPL	106 dB
Nominal Impedance	Selectable 8 ohms or 70/100V line
Dispersion	110° conical
Crossover	Inbuilt 2nd order cross over
Enclosure	ABS (UV stabilized)
Finish	UV Powder coated
Protective Grill	Perforated steel
Connectors	Push to fit
Pin connections	Input Red and black
Standard colour	White
Nominal/ AES Power	40 watts
Maximum/ Continuous/ Program Power	80 watts
Peak Power	160 watts
Backbox	None
High Pass	75 HZ
Mounting	Butterfly locks
Tapings	Selectable 20w/10w/6w
Product Dimensions (in mm)	240 x 80
Packing Dimensions (in mm)	255 x 272 x 108
Cut out dimensions (in mm)	205
Net Weight (kgs)	1
Shipping Weight (kgs)	2

Mid highs measured on-axis in full space @ one watt/1-meter using band-limited pink noise in the en-devour to continuously improve the product with design refinements introduced into existing products. Any current CSC product may differ in some respect from its published description. However, this will always equal or exceed the original design specifications. Every CSC Product is built to the highest standards and tested to ensure that it meets the performance criteria specified.

