



HARP SERIES MI 820D

Unmatched Clarity, Effortlessly Blended

The Harp MI 820D is a premium two-way coaxial ceiling speaker designed for controlled, full-range sound reinforcement. It features an 8" LF driver with a coaxially mounted tweeter for clear mids, smooth highs, and natural intelligibility. Its precision crossover eliminates tonal masking while maintaining balanced response.

Unlike the MI 820, the MI 820D includes a fully enclosed ABS back box, providing acoustic isolation and protection, making it ideal for

installations where ceiling cavity interaction must be minimized. Built with moisture-resistant materials, it is suited for restaurants, malls, conference rooms, and commercial venues. Installation is quick and clean—cut, connect, and drop in.

Its paintable finish ensures discreet integration into architectural spaces, leaving behind powerful, consistent sound for music or speech.

KEY FEATURES

- Compact, high performance two-way ceiling speaker
- High power 80 watt-nominal
- SPL 108 dB
- Frequency response from 90Hz to 18.5 kHz
- Brilliant for Music and vocal propagation
- Very smooth off-axis response-usable out to 120° (-6 dB)
- Fast, integral hardware

SYSTEM APPLICATIONS

- Distributed audio/public address system
- Component for commercial and retail
- Hotels, shopping malls
- Education and religious establishments
- Hospitals and conference rooms
- Restaurants and bars

MODEL NO	MI 820D
Type	Ceiling Speaker open Baffle
Frequency Response	90 Hz-18.5 kHz \pm 3 dB
Drivers	LF: 1 x 8" (200 mm) LF + Coaxially mounted Myler HF
Sensitivity (1 W / 1 m)	90 dB
Maximum SPL	108 dB
Nominal Impedance	Selectable 8 ohms or 70/100V line
Dispersion	100° from central axis
Crossover	Inbuilt 2nd order cross over
Enclosure	ABS (UV stabilized)
Finish	UV Powder coated
Protective Grill	Perforated steel
Connectors	Push to fit
Pin connections	Input Red and black
Standard colour	White
Nominal/ AES Power	80 watts
Maximum/ Continuous/ Program Power	160 watts
Peak Power	320 watts
Backbox	Yes
High Pass	75 HZ
Mounting	Butterfly locks
Tapings	Selectable 40w/20w/10w
Cut out dimensions (in mm)	245
Product Dimensions (in mm)	280 x 190
Packing Dimensions (in mm)	330 x 320 x 230
Net Weight (kgs)	3
Shipping Weight (kgs)	4

Mid highs measured on-axis in full space @ one watt/1-meter using band-limited pink noise in the en-devour to continuously improve the product with design refinements introduced into existing products. Any current CSC product may differ in some respect from its published description. However, this will always equal or exceed the original design specifications. Every CSC Product is built to the highest standards and tested to ensure that it meets the performance criteria specified.

