



HARP SERIES MI 820

Unmatched Clarity, Effortlessly Blended

The Harp MI 820 is a two-way coaxial ceiling speaker featuring an 8" LF driver with a coaxially mounted tweeter, engineered for exceptional clarity and full-range reinforcement in public spaces. Its optimally designed crossover ensures smooth integration, providing natural sound without bass masking.

The open-back design interacts with the ceiling cavity, adding warmth and depth to the low end, making it ideal for venues requiring fuller

presence. With superb off-axis coverage, it maintains intelligibility across wide areas, perfect for music and voice applications.

Built from moisture-resistant materials, the MI 820 is safe for use in restaurants, malls, and commercial spaces. Installation is simple: cut a hole, feed wires, and drop in. With a paintable finish, it blends seamlessly into décor, leaving only high-quality sound.

KEY FEATURES

- Compact, high performance two-way ceiling speaker
- High power 80 watts
- SPL 106 dB
- Frequency response from 80 Hz to 18.5 kHz
- Brilliant for music and vocal propagation
- Very smooth off-axis response - usable out to 100° (-6dB)
- Fast, integral hardware

SYSTEM APPLICATIONS

- Distributed audio/public address system
- Component for commercial and retail
- Hotels, shopping malls
- Education and religious establishments
- Hospitals and conference rooms
- Restaurants and bars
- VOG in home cinema

MODEL NO	MI 820
Type	Ceiling Speaker open Baffle
Frequency Response	80 Hz-18.5 kHz \pm 3 dB
Drivers	LF: 1 x 8" (200 mm) LF + Coaxially mounted Myler HF
Sensitivity (1 W / 1 m)	90 dB
Maximum SPL	106 dB
Nominal Impedance	Selectable 8 ohms or 70/100V line
Dispersion	100° from central axis
Crossover	Inbuilt 2nd order cross over
Enclosure	ABS (UV stabilized)
Finish	UV powder coated
Protective Grill	Perforated steel
Connectors	Push to fit
Pin connections	Input Red and black
Standard colour	White
Nominal/ AES Power	80 watts
Maximum/ Continuous/ Program Power	160 watts
Peak Power	320 watts
Backbox	Yes
High Pass	75 HZ
Mounting	Butterfly locks
Tapings	Selectable 40w/20w/10w
Cut out dimensions (in mm)	245
Product Dimensions (in mm)	280 x 100
Packing Dimensions (in mm)	300 x 300 x 120
Net Weight (kgs)	2
Shipping Weight (kgs)	3

Mid highs measured on-axis in full space @ one watt/1-meter using band-limited pink noise in the en-devour to continuously improve the product with design refinements introduced into existing products. Any current CSC product may differ in some respect from its published description. However, this will always equal or exceed the original design specifications. Every CSC Product is built to the highest standards and tested to ensure that it meets the performance criteria specified.

