

CONTRABASS RR 212s

Be it pounding night club or a live performance, the RR series has a set of reflex-loaded subwoofers. Each subwoofer has been designed to kick without losing their low-frequency extension. Suitable for use in fixed installation and mobile application, the RR series are extremely Versatile.

CSC RR 212s is loaded with dual 12" (300 mm) transducers with a power handling of a 1000 watt. **Require** a real compact **subwoofer**, RR 212s has **warmth and** accuracy suitable for use in fixed installation and mobile application. It has been specially designed for small live bands and lounges where power is required in a small footprint.

For demanding applications, the CSC Maestro MS 26 controller is configured to perform and its EQ and limiter functions are preloaded in the controller. CC 8, CF 10, CF 12, CF 15, CF 12h, RR 212h and RR 15h.



Key Features

- Baltic Birch ply construction
- Black non toxic texture paint
- Rubber feet
- Compact in size
- All weather grill
- Available in Black finish



Applications

- Auditoriums
- Concerts
- Places of Worship
- Pubs and Bars
- Night Clubs

Specifications	RR212s
Type	Compact, sub-bass system
Frequency response	37Hz - 250Hz ± 3dB
Dispersion	Omnidirectional
Nominal impedance	4 Ohms
Drivers	LF:2x12" (300mm)/ with 3" (75mm) voice coil LF driver
Horn	NA
Rated power	1000W
Recommended amplifier up to	1500W
Sensitivity 1w / 1m	101dB
Maximum SPL	131dB continuous 136dB peak
Crossover	100Hz active/ passive LPF
Enclosure	Baltic birch ply
Finish	Textured black paint
Protective grille	Perforated steel
Connectors	2 x Neutrik NI4
Pin connections	Input: + - 1, Link through: + - 2
Standard colours	Black
Fittings	Integral feet
Approvals	CE, ROHS
Dimensions including packing	910(W) x 570(H) x 760(D)
Dimensions product	850(W) x 510(H) x 730(D)
Net weight	68Kg

Mid highs measured on axis in full space @ 1 watt/1 meter using band limited pink noise. In the endeavour to continuously improve the product with design refinements introduced into existing products. Any current CSC product may differ in some respect from its published description. However this will always equal or exceed the original design specifications. Every CSC product is built to the highest standards and tested to ensure that it meets the performance criteria specified.

SAFETY INSTRUCTIONS

- ▶ When flying speakers, appropriate hardware and techniques must be employed for safely suspending the enclosures.
- ▶ Ensure all instructions that appear on specific loudspeaker datasheets are followed.
- ▶ All speaker hardware and flying apparatus must be regularly inspected for any visual or mechanical failure.
- ▶ Leave adequate distance between speakers and the audience. Refer to your local authority for Health and Safety guidance when using loudspeaker systems.
- ▶ The CSC digital controller should only be programmed by a CSC authorized technician. Do not use CSC loudspeaker systems without the correct controller and the program. If a system fails due to incorrect controller use, warranty is void.
- ▶ Protect your speakers and electronics from exposure to humidity, water or rain.
- ▶ CSC loudspeakers and electronics are covered against defects in workmanship or materials for a period of two years from the original date of purchase. The CSC warranty does not cover any item which in CSC's opinion has failed due to user abuse, accident, modifications.
- ▶ The defective item will be repaired/replaced with no charge for materials or labour. However the item should be adequately packed and dispatched, pre-paid, to a CSC authorized distributor/service center.