



CONTRABASS SERIES RR 212s

Compact Design, Massive Impact: Loudspeakers that Deliver

The Contrabass RR 212s is a low profile reflex loaded sub woofer. It is designed for applications where sub-woofers are easy to carry without compromising for power. The trend of high standard interiors in entertainment and catering venues requires sub-woofer concealment and minimal floor space. The sub woofer with its power handling of 800 watts can fill any venue with sound.

RR 212s Sub woofer adds deeper, more commanding bass to the systems performance. Its 2x12" long-excursion drivers pack all the power of a larger bass box into a more compact design that's easier to carry and fits in a car. The loudspeaker delivers high SPL performance while maintaining vocal clarity taking away the stress from the mid high. A mounting stand fits into the top hat between the sub woofer and mid high.

KEY FEATURES

- Compact, high-performance reflex loaded 2x12" sub-woofer
- Top hat for mounting mid high directly on the sub woofer
- Easy to install
- Can be retrofitted into existing venues

SYSTEM APPLICATIONS

- Small DJ's
- Small bands
- Lounges and Bars

MODEL NO	RR 212s
Type	Compact subwoofer
Frequency Response	45 Hz-250 Hz \pm 3 dB
Drivers	LF:2x12" (300mm)/ with 3" (77mm) voice coil LF driver
Recommended Amplifier Upto	1500 watts
Sensitivity (1 W / 1 m)	101 dB
Maximum SPL (9)	129 dB continuous, 135 dB peak
Nominal Impedance	4 ohms
Dispersion	Omni
Crossover	100 Hz active/ passive LPF
Enclosure	Baltic birch ply
Finish	Non-toxic Textured black paint
Protective Grill	Perforated steel
Connectors	2 x Neutrik NL4
Pin Connections	Input: \pm 1, Link through: \pm 2
Standard Colours	Black
Horn	NA
Nominal/ AES Power	800 watts
Maximum/ Continuous/ Program Power	1600 watts
Peak Power	3200 watts
Accessories	Castors, Speaker poles, felted waterproof covers
Dimensions - Product (in mm)	(W) 501 x (H) 498 x (D) 651
Dimensions - Including packing (in mm)	(W) 661 x (H) 537 x (D) 760
Net Weight (kgs)	39
Shipping Weight (kgs)	42

Mid highs measured on-axis in full space @ one watt/1-meter using band-limited pink noise in the en-devour to continuously improve the product with design refinements introduced into existing products. Any current CSC product may differ in some respect from its published description. However, this will always equal or exceed the original design specifications. Every CSC Product is built to the highest standards and tested to ensure that it meets the performance criteria specified.

