



CONTRABASS SERIES RR 218s

Engineered for Impact: Experience Bass Like Never Before!

This reflex-loaded, 2000 watts, dual 18" (450mm) sub-woofer is the main system to be used with the Cello series top cabinets.

Perfect for use in fixed installation and mobile application, the RR 218s is an extremely versatile sub-woofer for integrators. It has been specially designed keeping live bands in mind.

For demanding applications, the CSC Maestro MS 26 controller is configured to perform with its EQ and limiter functions are pre-loaded in the controller.

CC 8, CF 10, CF 12, CF 15, CF 12h, RR 212h and RR 15h are a perfect match for RR 218s.

KEY FEATURES

- Compact, high-performance, multi-load dual 18" sub-woofer
- Easy to install
- Can retrofit into existing venues
- Rubber feet & top hat

SYSTEM APPLICATIONS

- Concerts and live performances
- Nightclubs

MODEL NO	RR 218s
Type	Reflex loaded subwoofer
Frequency Response (1)	34 Hz-300 Hz \pm 3 dB
Drivers	LF: 2 x18" (450 mm) with a 4" (100 mm) voice coil
Recommended Amplifier Upto	3000 watts
Sensitivity (1 W / 1 m)	102 dB
Maximum SPL (9)	133 dB continuous, 139 dB Max
Nominal Impedance	4 ohms
Dispersion	Omni
Crossover	LPF 100 Hz
Enclosure	Baltic birch ply
Finish	Non-toxic Textured black paint
Protective Grill	Perforated steel
Connectors	2 x Neutrik NL8
Pin Connections	Input : \pm 1, Link through: \pm 2
Standard Colours	Black
Horn	NA
Nominal/ AES Power	2000 watts
Maximum/ Continuous/ Program Power	4000 watts
Peak Power	8000 watts
Accessories	Castors, Felted waterproof covers, Speaker poles
Dimensions - Product (in mm)	(W) 1197 x (H) 559 x (D) 787
Dimensions - Including packing (in mm)	(W) 1215 x (H) 595 x (D) 815
Net Weight (kgs)	84
Shipping Weight (kgs)	95

Mid highs measured on-axis in full space @ one watt/1-meter using band-limited pink noise in the en-devour to continuously improve the product with design refinements introduced into existing products. Any current CSC product may differ in some respect from its published description. However, this will always equal or exceed the original design specifications. Every CSC Product is built to the highest standards and tested to ensure that it meets the performance criteria specified.

