







## STRING SERIES ST 3

Compact Design, Massive Impact: Loudspeakers that Deliver

The ST 3 from CSC's String Series is an ultracompact passive loudspeaker built for crystalclear background and ambient sound in architecturally sensitive spaces. With a 3" fullrange driver housed in a rigid extruded aluminum enclosure without parallel walls, it eliminates resonances while ensuring accurate projection and even coverage.

Designed for near-field listening, it provides balanced mids, smooth highs, and low distortion, making it perfect for restaurants, boutiques, galleries, foyers, and lounges. Its sleek, minimalist design allows horizontal or vertical mounting with an omni-directional bracket for walls or ceilings.

Available in black or white matte finishes, it integrates seamlessly into interiors. Used alone or paired with a compact subwoofer, the ST 3 offers discreet, high-quality sound reinforcement without cluttering visual aesthetics.

## **KEY FEATURES**

- · Ultra-compact design
- High-efficiency transducers
- · Clean, architectural styling
- · Consistent voicing across models
- · Flexible mounting options

## SYSTEM APPLICATIONS

- · Retail spaces and boutiques
- · Art galleries and museums
- · Hospitality and leisure environments
- · Houses of worship and conference rooms



MODEL NO	ST 3
Туре	Ultra compact satellite
Frequency Response (1)	150 Hz-16 kHz ± 3 dB
Drivers	LF. 3" (77 mm) neo driver
Recommended Amplifier Upto	40 watts
Sensitivity (1 W / 1 m)	91 dB
Maximum SPL (9)	104 dB continuous, 110 dB Max
Nominal Impedance	8 ohms
Dispersion	90° conical
Crossover	HPF Hz ( 170Hz)
Enclosure	Extruded Aluminium
Finish	Powder Coated
Protective Grill	Perforated steel
Connectors	2 x Phoenix connectors
Pin Connections	Input: ± 1, Link through: ± 2
Standard Colours	Black / White
Fittings	Rear mounting
Horn	NA
Nominal/ AES Power	20 watts
Maximum/ Continuous/ Program Power	40 watts
Peak Power	80 watts
Accessories	Clamp
Dimensions - Product (in mm)	(W) 116 x (H) 90 x (D) 138
Dimensions - Including packing (pair) (in mm)	(W) 290 x (H) 150 x (D) 195
Net Weight (kgs)	1
Shipping Weight (kgs)	3 (Shipped in pairs)

Mid highs measured on-axis in full space @ one watt/1-meter using band-limited pink noise in the en-devour to continuously improve the product with design refinements introduced into existing products. Any current CSC product may differ in some respect from its published description. However, this will always equal or exceed the original design specifications. Every CSC Product is built to the highest standards and tested to ensure that it meets the performance criteria specified.





